

	SINTONIZADOR DIGITAL TERRESTRE TV ISDB-T	
	BRAND	ISDB-T
	MODEL	HD DVB-T2
	Product photo, package photo	
	Specifications	168*90*36MM
	Case	plastic/metal
	Chipset	ALI3821P
	Tuner	R850
	Flash	4MByte
	DDR	built in 64MB DDR2
	Dolby Digital	N/A
	LED display	YES
	EPG	YES
	Time Shift	YES
	PVR	YES
High Frequency Tuner	RF input frequency	V BAND 177-213MHZ, U BAND 473-863MHZ
	RF input level	-82dBm (256QAM R2/3 G1/128 PP7 32KE No-PAPR)
	Bandwidth	6M
	Input Impedance	75Ω
Demodulation	Waveform	
	Demodulation	BUILT IN
	Guard Interval	1/128 to 1/4
	Code Rate	1/2,2/3,3/5,3/4,4/5,5/6,2/5,1/3
Video Decoding	Video Decoder format	MP4/MKV/ MOV/AVI/TS/MPG
	Video Resolution	1920x 1080P, 1920x 1080i, 1280x 720p, 720x 576p, 720x 576i 720x 480p,720x480i
	Video Input Code Rate	MEPG2:1080P@30pfs H.264:1080P@30pfs VC1:2048x 1024P30 max rate:20Mbps
	Video Output Ratio	1080i 50HZ
	Picture Signal System	
Audio	Audio Decoding	MPEG-1, MPEG-2(Layer I/II), AAC, HE-AAC, AC-3,DTS,
	Audio Track	ex. Stereo, Dual Track, Monophony
	Supported file formats	.MP3/.WMA/AAC
	Aspect ratio	16:9/4:3
	Picture Format	PNG/BMP/JPG
	File Management System	ntfs/fat32
	Output Current	
	Rated Voltage	100-240V 50-60HZ
	Max power consumption	5W
	Max Standby power consumption	<1W
	Operated temperature range	-10--+80℃
	Interfaces	HDMI 1.4, USB 2.0, RCA,COAXIAL
	Package Contents (Accessory)	
	Product size (L x W x H)	185*160*48MM
	Package size (L x W x H)	510*385*335MM
	N.W/giftbox (kgs)	17.7 kgs
	G.W/giftbox (kgs)	18.5 kgs
	Qnty per package	40pcs